

DPMS Panther Arms

PANTHER™ CARBINE (RFA2-PCAR)

Barrel:

- 11.5" 4140 Chrome-moly steel, 5 1/2" Flash hider
- Manganese phosphated
- 6 groove, right-handed 1x9 twist, button rifled

Chamber:

- 5.56 x 45mm

Method of Operation:

- Gas operated rotating bolt

Bolt & Carrier:

- Phosphated 8620 steel bolt & bolt carrier, heat treated and plated per Mil Spec.

Sights:

- Standard A2 front sight assembly

Weight:

- Empty - 6.9 lbs

Length:

- Extended - 35 1/2"
- Collapsed - 31 3/4"

Upper Receiver:

- Forged 7075-T6 aircraft aluminum alloy
- Hard coat anodized per Mil Spec and Teflon coated black
- A2 fixed carry handle and rear sight adjustable for windage and elevation.
- Dust cover
- Shell deflector
- Round forward assist
- Right hand ejection

Lower Receiver:

- Forged 7075-T6 aircraft aluminum alloy
- Hard coat anodized per Mil Spec and Teflon coated black
- Semi-auto trigger group
- Aluminum trigger guard
- Magazine release button

Stock:

- Telescoping fiber reinforced



This rifle is unavailable for online order, please call DPMS or your local FFL Dealer to purchase this rifle.

MSRP: \$799.00

Pre Ban rifles and high capacity magazines are unavailable in the following states: California, Hawaii, Maryland, Massachusetts, New Jersey & New York

polymer AP4 (6 position)

Handguards:

- GlacierGuards™
- Oval carbine length
- Aluminum delta ring

Options:

- CRYO Barrel Deep Freeze
- Free float aluminum handguards (16" barrel only)
- Harris bipod
- Chrome or Titanium Bolt Carrier Assembly
- JP Adjustable Trigger
- Free float 4-rail handguards

Note:

Bipod not included.
Each rifle comes with 2- 30 rd.
Magazines, 1- Nylon Web Sling
and 1- Cleaning Kit

PANTHER™ LR-308 AP4 16" AP4 CARBINE (RFLR-AP4)

Barrel:

- 16" Heavy barrel, with a mock AP4 contour
- 4140 Chrome-moly steel
- 6 grooves, right-handed 1x10 twist, button rifled
- 308 Panther Flash Hider

Chamber:

- .308 Winchester

Method of Operation:

- Gas operated rotating bolt

Bolt & Carrier:

- 8620 chrome-plated steel bolt carrier, heat treated per Mil Spec.
- Phosphated 8620 steel bolt, heat treated and plated per Mil Spec.

Sights:

- Standard A2 front sight assembly
- Detachable rear sight (FT-RS)

Weight:

- Empty - 8.5 lbs

Length:

- Extended - 35.6"
- Collapsed - 31.6"

Upper Receiver:

- A3-style Flattop
- Thick walled, extruded from 6066-T6 aluminum
- Hard coat anodized per Mil Spec and Teflon coated black
- Snag free design, smooth side look
- Dust cover
- Shell deflector
- Round forward assist
- Right hand ejection
- Standard sight base

Lower Receiver:

- Milled from a solid billet of 6061-T6 aluminum
- Hard coat anodized per Mil Spec and Teflon coated black
- Standard A-15 trigger group
- Integral trigger guard
- Aluminum magazine release button

Stock:

- AP4 - 6 position, telescoping fiber reinforced polymer

Handguards:

- Ribbed aluminum free float
- 2.24" Outside diameter
- 7.25" in length

Note:

Bipod not included.

Each rifle comes with 2- 19 rd. Steel Magazines, 1- Nylon Web Sling and 1- Cleaning Kit